

Pinnacle Dryer Corporation
330 Fields Drive
Aberdeen, North Carolina 28315
1-800-943-7937*910-944-2117*Fax 910-944-9430
www.pinnacledryer.com

GENERAL SPECIFICATIONS FOR THE P3-12S

THE BRAND AND MODEL NUMBER SHOWN ARE TO ESTABLISH THE LEVEL OF QUALITY EXPECTED FOR THIS REQUIREMENT. THE P3-12S SURFACE HAND DRYER AS MANUFACTURED BY PINNACLE DRYER CORPORATION WILL BE THE BENCHMARK. OTHER BRANDS WILL BE CONSIDERED IF THEY MEET THE FUNCTIONALITY, OPERATION AND RUGGEDNESS REQUIRED.

The dryer shall be touchless and activated by an infra-red light. The machine shall run only for the time during which the user's hands are inside the drying chamber. No button shall be required. Hands shall fit into a recessed cavity where the warm air is recycled, allowing a quick drying time of 20-25 seconds.

The dryer is ADA Compliant and shall enhance the environmental goals of sanitation and reduction of bacteria by not requiring the user to touch any controls.

Overheat protection should be provided by state-of-the-art circuitry, featuring an automatic cut off which activates after 60 seconds of continuous running. The hand dryer shall reset itself once any obstruction is removed.

The dryer shall be surface mounted. The cover shall be made of 20 gauge stainless steel. The cover shall be attached with ¼ x 20 x ¾ Torx w/pin button screws. Knockout shall be provided on top of the cover. The dryer shall be capable of mounting on any surface wall. The machine shall draw 11 AMPS at 120 Volts nominal.

Dryer shall be ADA Compliant.

THE P3-12S HAND DRYER IS A UNIQUE, STATE-OF-THE-ART HAND DRYER. PLEASE CALL 1-800-943-7937 FOR A QUOTATION.