

Pinnacle Dryer Corporation
330 Fields Drive
Aberdeen, NC 28315
1-800-943-7937*Fax 910-944-9430

GENERAL SPECIFICATIONS FOR PDC-R10

THE BRAND AND MODEL NUMBER SHOWN ARE TO ESTABLISH THE LEVEL OF QUALITY EXPECTED FOR THIS REQUIREMENT. THE PDC-R10 RECESSED HAND DRYER AS MANUFACTURED BY PINNACLE DRYER CORPORATION WILL BE THE BENCHMARK. OTHER BRANDS WILL BE CONSIDERED IF THEY MEET THE FUNCTIONALITY, OPERATION AND RUGGEDNESS REQUIRED.

The dryer shall be touchless and activated by an infra-red light. The machine shall only run for the time during which the user's hands are inside the drying chamber. No button shall be required. Hands shall fit into a recessed cavity where the warm air is recycled, allowing a quick drying time of 20-25 seconds.

The dryer shall enhance the environmental goals of sanitation and reduction of bacteria by not requiring the user to touch any controls.

Overheat protection should be provided by state-of-the-art circuitry, featuring an automatic cut off which activates after 60 seconds of continuous running. The hand dryer shall reset itself once any obstruction is removed.

The dryer shall be totally recessed. Cover and drying chamber shall be made of 18 gauge stainless steel. The cover shall be made of 18 gauge stainless steel. The cover shall be attached with (4) 1/4-20 stainless steel security screws. Knockouts shall be provided on top and bottom of recessed box. The dryer shall be capable of mounting in either a 6" or 8" block wall or a 4" stud wall. Mounting brackets are attached to recessed box on outside wall. The bottom of the recessed box is 4 5/8" from the bottom of the mounting brackets. The machine shall draw 11.5 AMPS at 120 Volts nominal.

Dryer shall be ADA compliant.

THE PDC-R10 HAND DRYER IS A UNIQUE, STATE-OF-THE-ART HAND DRYER. PLEASE CALL 1-800-943-7937 FOR A QUOTATION .